

MySentio Remote

Description

MySentio Remote

1-053-314 / S-WIFI02

Start your sauna and steam bath through your mobile.

Innovative technology:

- Mobile use and cloud technology
- WiFi connected (easy connection and setup)
- Status functions available (on/off)
- For all control units with potential-free remote start input (sauna, infrared and steam bath control units)

Operating a sauna heater using a remote start function requires appropriate safety precautions to be taken (e.g. safety shutdown or door monitoring)



Compatible sauna control units:

wave.com4 11kW (1-049-633 / WC4-B-11)

SGH (1-050-578 / SGH-45; 1-050-579 / SGH-60; 1-050-580 / SGH-90; 1-050-581 / SGH-110; 1-050-582 / SGH-150)

HGD (1-047-553 / HGD45; 1-047-558 / HGD60; 1-047-559 / HGD90; 1-047-560 / HGD110; 1-047-561 / HGD150)

home.com4 (1-040-275 / HC4-B ; 1-040-276 / HC4-W)

Pro B2 (1-015-455 / PRO-B2)

Pro B3 (1-015-457 / PRO-B3)

Pro C2 (1-015-448 / PRO-C2)

Pro C3 (1-015-451 / PRO-C3)

Pro D2 (1-041-288 / PRO-D2)

Pro D2i (1-041-291 / PRO-D2i)

Pro D3 (1-041-293 / PRO-D3)

Pro D3i (1-041-295 / PRO-D3i)



Optional accessories:

- Cut-off rocker switch (SFE-xxxx)
(rectangular: 220x400 mm 1-045-582 / SFE-220400, 350x400 mm 1-045-583 / SFE-350400 oder 500x500 mm 1-045-588 / SFE-500500, round / diameter: 350 mm 1-045-806 / SFE-D350, 450 mm 1-045-805 / SFE-D450 oder 530 mm 1-045-585 / SFE-D530)
- Doorsensor-system (1-052-722 / SAB00102)
- Doorsensor-set (1-052-723 / SAB00103)
- Power supply LED 40W / 24VDC (1-052-972 / LED-PWS-24-40)
- BUS-Converter for PRO D (BUS-CON-D)



MySentio Remote

Technical data Extension Box:

- Dimensions: 85 x 85 x 37 mm
- Switching capacity: 24V DC max. 3W
- Minimum requirement WLAN 2,4GHz: 1Mbit

AMBIENT CONDITIONS:

- Ambient temperature: -0° C to +70° C
- Protection class: IP65

CONNECTING CABLES:

- Power supplied via screw terminal Power supply LED 40W / 24V (1-052-972 / LED-PWS-24-40)
OR
- Ethernet cable: 8 Polig RJ45 max.30m

Technical data MySentio WiFi:

- Dimensions: 83 x 56 x 42,5 mm
- Minimum requirement WLAN 2,4GHz: 1Mbit

AMBIENT CONDITIONS:

- Ambient temperature: -20° C to +40° C
- Protection class: IP20

CONNECTING CABLES:

- Ethernet cable: 8 Polig RJ45 max.30m



MySentio Remote

Beschreibung

MySentio Remote 1-053-314 / S-WIFI02

Starten Sie Ihre Sauna und Ihr Dampfbad von unterwegs.

Innovative Technik:

- Mobile Nutzung und Cloud Technik
- WiFi verbunden (einfache Verbindung und Einrichtung)
- Statusfunktionen verfügbar (eingeschaltet)
- Für alle Steuergeräte mit potenzialfreiem Fernstarteingang (Sauna-, Infrarot- und Dampfbadsteuerungen)
- Low Power Technologie

Um einen Saunaofen mittels Fernstartfunktion betreiben zu können, müssen entsprechende Sicherheitsvorkehrungen getroffen werden (zB. Abschaltwippe oder Türüberwachung).



Kompatible Steuerungen:

wave.com4 11kW (1-049-633 / WC4-B-11)

SGH (1-050-578 / SGH-45; 1-050-579 / SGH-60; 1-050-580 / SGH-90; 1-050-581 / SGH-110; 1-050-582 / SGH-150)

HGD (1-047-553 / HGD45; 1-047-558 / HGD60; 1-047-559 / HGD90; 1-047-560 / HGD110; 1-047-561 / HGD150)

home.com4 (1-040-275 / HC4-B ; 1-040-276 / HC4-W)

Pro B2 (1-015-455 / PRO-B2)

Pro B3 (1-015-457 / PRO-B3)

Pro C2 (1-015-448 / PRO-C2)

Pro C3 (1-015-451 / PRO-C3)

Pro D2 (1-041-288 / PRO-D2)

Pro D2i (1-041-291 / PRO-D2i)

Pro D3 (1-041-293 / PRO-D3)

Pro D3i (1-041-295 / PRO-D3i)



Optionales Zubehör:

- Abschaltwippe (SFE-xxxx)
(eckig: 220x400 mm 1-045-582 / SFE-220400, 350x400 mm 1-045-583 / SFE-350400 oder 500x500 mm 1-045-588 / SFE-500500, rund / Durchmesser: 350 mm 1-045-806 / SFE-D350, 450 mm 1-045-805 / SFE-D450 oder 530 mm 1-045-585 / SFE-D530)
- Türsensor-System (1-052-722 / SAB00102)
- Türsensor-Set (1-052-723 / SAB00103)
- Netzteil LED 40W / 24VDC (1-052-972 / LED-PWS-24-40)
- BUS-Converter für PRO D (BUS)



MySentio Remote

Technische Daten Extension Box:

- Gehäuseabmessungen: 85 x 85 x 37 mm
- Betriebsspannung: 24V DC max. 3W
- Mindestanforderung WLAN 2,4GHz: 1Mbit

UMGEBUNGSBEDIENUNGEN:

- Umgebungstemperatur: -0° C to +70° C
- Schutzart: IP65

ANSCHLUSSLEITUNGEN:

- Spannungsversorgung mittels Netzteil (1-052-972 / LED-PWS-24-40)
ODER
- Ethernetkabel: 8 Polig RJ45 max.30m

Technische Daten MySentio WiFi:

- Gehäuseabmessungen: 83 x 56 x 42,5 mm
- Mindestanforderung WLAN 2,4GHz: 1Mbit

UMGEBUNGSBEDIENUNGEN:

- Umgebungstemperatur: -20° C to +40° C
- Schutzart: IP20

ANSCHLUSSLEITUNGEN:

- Ethernetkabel: 8 Polig RJ45 max.30m

